

Product Name: BT968



Processor	<p>Intel Atom® Processor E3800 Series, BGA 1170</p> <p>Intel Atom® E3845, Quad Core, 2M Cache, 1.91GHz, 10W</p> <p>Intel Atom® E3827, Dual Core, 1M Cache, 1.75GHz, 8W</p> <p>Intel Atom® E3815, Single Core, 0.5M Cache, 1.46GHz, 5W</p> <p>Intel® Celeron® J1900, Quad Core, 2M Cache, 2GHz (2.41GHz), 10W</p> <p>Intel® Celeron® N2930, Quad Core, 2M Cache, 1.83GHz (2.16GHz), 7.5W</p>
Part Number	BT968
Memory	<p>Two 204-pin SODIMM up to 8GB</p> <p>Dual Channel DDR3L 1333MHz</p>
BIOS	AMI 64Mbit BIOS
Controller	Intel® HD Graphics
Feature	<p>OpenGL 3.2, DirectX 11, OpenCL 1.2</p> <p>HW Decode: AVC/H.264, MPEG2, VC1, WMV9, JPEG/MJPEG, HEVC/H.264, VP8, VP9, MVC</p> <p>HW Encode: AVC/H.264, JPEG/MJPEG, HEVC/H.264, VP8, VP9, MVC</p>
Display	<p>1 x DDI (HDMI/DVI/DP)</p> <p>1 x LVDS/DDI* (HDMI/DVI/DP)</p> <p>1 x VGA</p> <p>LVDS: dual channel 24-bit, resolution up to 1920x1200 @ 60Hz</p> <p>HDMI/DVI: resolution up to 1920x1080 @ 60Hz</p> <p>DP: resolution up to 2560x1600 @ 60Hz</p> <p>VGA: resolution up to 1920x1200 @ 60Hz</p>
Expansion	<p>3 x PCIe x1 or 1 PCIe x4</p> <p>1 x LPC</p> <p>1 x I2C</p> <p>1 x SMBus</p> <p>2 x Serial (TX/RX)</p>



Audio	HD Audio
Ethernet	1 x Intel® I210AT (10/100/1000Mbps)
USB	1 x USB 3.0 8 x USB 2.0
Storage	2 x SATA 2.0
eMMC	1 x 4GB/8GB/16GB/32GB eMMC (available upon request)
DIO	1 x 8-bit DIO
Power	12V, 5VSB, VCC_RTC (ATX mode) 12V, VCC_RTC (AT mode)
OS Support	Windows 7 Ultimate x86 & SP1 (32-bit) Windows 7 Ultimate x64 & SP1 (64-bit) Windows 8 Enterprise x86 (32-bit) Windows 8 Enterprise x64 (64-bit) Windows 8.1 Enterprise x86 (32-bit) Windows 8.1 Enterprise x64 (64-bit) Windows 10 Enterprise x86 (32-bit) Windows 10 Enterprise x64 (64-bit)
Operating Temperature	Operating: 0 to 60°C, -20 to 70°C, -40 to 85°C
Dimensions	COM Express® Compact 95mm (3.74") x 95mm (3.74")
Compliance	PICMG COM Express® R2.1, Type 6